

RAILWAY TRACK FAULT DETECTION SYSTEM

PRAGNA SHREE S A

Department of Electronic and Communication Engineering
C. Byre Gowda Institute of Technology, Kolar, India
Email: pragnagowda17@gmail.com

PRATHIMA M

Department of Electronic and Communication Engineering
C. Byre Gowda Institute of Technology, Kolar, India
Email: prathima.35m@gmail.com

DHANUSH S

Department of Electronic and Communication Engineering
C. Byre Gowda Institute of Technology, Kolar, India
Email: ghanushs2580@gmail.com

NAVEEN B S

Department of Electronic and Communication Engineering
C. Byre Gowda Institute of Technology, Kolar, India
Email: naveenbs552@gmail.com

Abstract: Railway track safety is a critical factor in preventing accidents and ensuring reliable train operations. Traditional methods of railway track inspection are largely manual, time-consuming, and prone to human error, which may lead to undetected faults and delayed maintenance. This project presents an automated Railway Track Fault Detection System using an embedded platform to improve inspection efficiency and safety. The proposed system employs an Arduino Uno microcontroller as the central control unit, along with sensors such as IR/ultrasonic sensors to detect cracks, gaps, or obstacles on the railway track. A motor-driven inspection vehicle moves along the track while continuously monitoring track conditions. When a fault is detected, the system immediately stops the vehicle and activates alert mechanisms. The exact location of the detected fault is obtained using a GPS module and transmitted to a predefined mobile number through a GSM module. This system reduces manual inspection effort, enables early fault detection, and provides real-time location-based alerts. Due to its low cost, simplicity, and reliability, the proposed solution is suitable for educational purposes and small-scale railway monitoring applications, with potential for future enhancements using advanced sensors and intelligent algorithms.

Keywords: Railway Track Fault Detection, Automation, Ultrasonic & IR Sensors, Arduino Microcontroller, GSM & GPS Modules.

I. INTRODUCTION

Railway is one of the most significant transportation modes of our country, but it is a matter of great sorrow that railway tracks of our country are very prone. That's why a vast number of accidents occur every year due to this primitive type of railway tracks and as the consequences of those accidents lose huge number of

lives every year. These types of incidents motivate us to think over the above-mentioned issue and take necessary steps to protect those lives. Through our as a motivational parameter to design the model. Moreover, natural disaster can throw any object on the rail track which cannot be removed very quickly in the remote area.

We thought if our system can detect those object or barrier and inform the control room then they can take necessary steps to avoid accidents and depict the fault on track. The Rail transport is growing at a rapid pace in India. It is one of the major modes of transport but still our facilities are not that accurate, safer as compared to international standards. A survey on the internet states that about 60% of all the railway accidents is due to derailments, recent measurements shows that about 90% are due to faults on the rails. Hence, it is not safer for Human Life. This needs to be at the utmost attention. These go unnoticed and the proper maintenance of tracks is not done.

In previously existing system, the work is to be done manually, but the proposed system has a robot which will run automatically on the tracks. System having LED and LDR sensor assembly, but the main disadvantage is that the LED and LDR must be placed opposite each other and also the environment needs to be perfect to detect the track. To overcome this disadvantage, here sensors are used, which will detect the crack accurately. The existing system is slow, tedious and time consuming. This system has GSM and GPS modules which will give the real time location or coordinates in the form of Short Message Service (SMS) to the nearest railway station.

II. MATERIAL AND METHODOLOGY

A. System Design

The system design of the Railway Track Fault Detection System is structured around an embedded and automated monitoring framework that integrates sensing, processing, and communication units. The core component of the system is the Arduino Uno microcontroller, which acts as the central processing unit. It is responsible for receiving inputs from sensors, processing data, and controlling the output devices.

The system is mounted on a robotic vehicle that moves along the railway track using DC motors. These motors are controlled through an L293D motor driver, which enables bidirectional movement and proper speed control. The movement of the vehicle ensures continuous inspection of railway tracks without manual intervention.

For fault detection, ultrasonic sensors are used as the primary sensing components. These sensors continuously scan the track by transmitting ultrasonic waves and analysing the reflected signals. Any variation in the expected distance indicates the presence of cracks, gaps, or obstacles on the track. The sensor data is sent to the Arduino, where it is compared with predefined threshold values to determine whether a fault exists.

Once a fault is detected, the system triggers multiple response mechanisms. The Arduino immediately stops the motor to halt the vehicle. At the same time, a buzzer and LED indicators are activated to provide local alerts. To enable remote communication, the system incorporates a GSM module, which sends an SMS notification to the concerned authorities. Additionally, a GPS module is used to capture the exact location coordinates of the detected fault, ensuring accurate fault identification.

The overall design follows a modular approach, where each component performs a specific function while working in coordination with others. This system design ensures real-time monitoring, quick fault detection, and efficient communication, making it a reliable and cost-effective solution for improving railway safety.




Fig. 1. Block diagram of the proposed system

B. Working Methodology

The Railway Track Fault Detection System is an automated system designed to identify faults such as cracks, misalignment, or obstacles on railway tracks and alert the authorities in real time. The working process begins when power is supplied to the system, activating all hardware components including the Arduino Uno microcontroller, sensors, motor, GPS, and GSM modules. The Arduino Uno acts as the central control unit, coordinating all operations of the system.

Once the system is powered on, the sensors—primarily ultrasonic sensors—are activated to continuously monitor the condition of the railway track. These sensors work by emitting ultrasonic waves and receiving the reflected signals. By calculating the time taken for the waves to return, the system determines the distance to any object or irregularity present on the track. If there is any abnormal variation in distance, such as a crack, gap, or obstacle, the sensor detects it as a fault.

Simultaneously, the robotic vehicle, which is mounted on wheels and powered by a DC motor, begins to move forward along the railway track. The motor is controlled by the Arduino through a motor driver (L293D), ensuring smooth and controlled movement. As the vehicle moves, the sensors continuously scan the track surface in real time.

During operation, the system constantly checks whether any fault is detected. If no fault is found, the vehicle continues moving forward while monitoring the track. However, if a fault is detected, the Arduino immediately processes this input and takes necessary actions. First, it stops the vehicle to prevent further movement and avoid potential damage or inaccurate readings.

Next, the system activates the GPS module to determine the exact geographical location (latitude and longitude) of the detected fault. This ensures precise identification of the problem area. After obtaining the location data, the GSM module is activated. The GSM module sends an SMS alert containing the

fault information and GPS coordinates to a predefined mobile number, such as the railway control room or maintenance team.

In addition to sending alerts, the system also activates a buzzer and LED indicators to provide local audio and visual warnings. This helps nearby personnel immediately recognize that a fault has been detected.

After sending the alert, the system can either reset itself to continue monitoring or stop its operation based on the programmed instructions. This entire process ensures continuous inspection of railway tracks without human intervention.

Overall, the working process of this system is fully automated, efficient, and reliable. It enables early detection of faults, reduces dependency on manual inspection, and ensures quick communication with authorities. By combining sensing, processing, and communication technologies, the system significantly enhances railway safety and helps prevent accidents, ultimately saving lives and reducing maintenance costs.

III. RESULT AND DISCUSSION

Currently GSM module, IR sensor, motor driver and motor are interfaced with microcontroller. All the components are performing the task as desired and the message is sent 'Obstacle present' via GSM module, whenever presence of obstacle is detected. For the testing purpose IR sensor was used. Now is replaced with Ultrasonic sensor in order to get better sensitivity i.e. It will detect even the small change in distance between the sensor and obstacle present in front of it which will make our device more preferable. Now only GPS module is to be interfaced to get the coordinates of the place

where there'll be crack found in the middle of tracks, Message received from GSM Module Further changes are to be done in the program so the GPS coordinates to be sent as SMS using GSM module. capacitor.



Fig.2.1 Project Outlook




Fig.2.2 Longitude and Latitude Fault Detection

The Railway Track Fault Detection System is designed to improve railway safety by enabling early detection of track defects through automation. Railway tracks are subjected to heavy loads, weather variations, corrosion, and aging, which can cause faults such as cracks, misalignment, breakage, loose joints, and obstacles. Traditional manual inspection methods are slow, costly, and prone to human error, making an automated system essential. This system continuously monitors track conditions using sensors like ultrasonic and infrared sensors, which detect abnormalities such as distance changes or interruptions. The collected data is processed by a microcontroller, which compares it with predefined threshold values to identify faults. When a fault is detected, the system immediately triggers alerts using a GSM module and provides the exact fault location through a GPS module, enabling quick maintenance action. Additional components like buzzers, LEDs, and LCD displays provide local alerts and system status. The system offers real-time monitoring, accurate fault detection, and reduces dependency on manual inspection, making it cost-effective in the long run. It significantly enhances safety and reliability by detecting faults before they lead to major failures and by reducing response time for maintenance, ensuring smooth and secure railway operations.

IV. CONCLUSION

The Railway Track Fault Detection System provides an effective and reliable solution for identifying defects such as cracks, misalignments, and breaks in railway tracks at an early stage. By using sensors, microcontrollers, and communication

technologies, the system continuously monitors track conditions and detects faults in real time. This helps in preventing major accidents, reducing derailments, and ensuring the safety of passengers and railway assets.

The automated nature of the system minimizes the need for manual inspection, thereby saving time, labor, and maintenance costs. It also improves the efficiency of railway operations by enabling quick response and timely maintenance. Overall, the Railway Track Fault Detection System enhances safety, reliability, and operational performance of railway networks, making it a vital technology for modern railway infrastructure.

Overall, this project proves that sensor-based and embedded systems can play a vital role in improving railway infrastructure safety. With further enhancements such as advanced sensors, wireless data logging, and machine learning integration, the system can be scaled for real-world railway applications and continuous monitoring.

REFERENCES

- [1]. W. Kou, Y. Song, W. Guo, H. Wang, X. Sun, and X. Gao, "Railway track defect detection using an improved YOLO11 algorithm," *Scientific Reports*, vol. 15, p. 14963, 2025, doi: 10.1038/s41598-025-14763-w.

- [2].] G. Rakesh, P. V. Reddy, P. Vardhan, and C. Sai, "Detection of railway track fault using machine learning techniques," *Sensors*, vol. 21, no. 6221, 2021, doi: 10.3390/s21186221.
- [3]. S. Sharma, K. Rajesh, and D. Singh, "Acoustic-based railway track fault detection using machine learning algorithms," *Sensors*, vol. 23, no. 7018, 2023, doi: 10.3390/s23127018.
- [4]. S. Sharma, K. Rajesh, and D. Singh, "Acoustic-based detection of railway track defects using MFCC and machine learning classifiers," *Sensors*, vol. 25, no. 2371, 2021, doi: 10.3390/s25052371.
- [5]. S. Dhar and P. Dutta, "Railway track fault detection system using Constant-Q Transform and machine learning models," *International Journal of Creative Research Thoughts (IJCRT)*, vol. 12, no. 4, pp. 315–319, 2024.
- [6]. P. Bansal and J. Kaur, "IoT based railway track fault detection system," *International Journal of Research in Engineering and Technology*, vol. 7, no. 19, pp. 95–100, 2019.
- [7]. P. Mohan and R. Singh, "Railway track crack detection using robotic vehicle," *International Journal of Engineering Research and Applications*, vol. 6, no. 12, pp. 35–40, 2016.
- [8]. H. Gou, H. Chen, and J. Zhang, "Review of vision-based railway track inspection methods," *Journal of Imaging*, vol. 10, no. 192, pp. 1–20, 2020, doi: 10.3390/jimaging10020192.